

LAKELINE LLC

Part # SW-EZ91-BP-087 & SW-EZ9E-BP-097 +1
Magazine Extension and Pinky Extension Installation
Instructions for Smith & Wesson EZ9:

Tools:

- 0.050" Allen Wrench
- Safety Glasses

Procedure:

- Put on your safety glasses.
- Check that pistol is unloaded and remove magazine.
- Using a non-marring instrument, depress the round boss on the base retainer on the bottom of the magazine. Contain things carefully on this step, because the spring will attempt to vigorously decompress as you remove the base plate. While depressing the boss, carefully slide the base plate towards the front of the mag and remove it and the base plate retainer.
- For the +1 extension to allow the extra round, the magazine load assist tabs must be removed from the follower. The part is circled in red in the photo. Just remove the spring and follower and slide it out.



- Next, hold the magazine in one hand while compressing the magazine spring with your thumb. Take the new magazine extension and slide it onto the magazine. The spring will click as it moves down into the base plate when it is fully installed.
- Use your 0.050 inch Allen wrench to install the retaining screw into the mating hole on the magazine extension (marked with arrow below). Just tighten the set screw until the base is tight and won't slide on the magazine. Do not tighten it further.:



That's it! You can now remove your safety glasses. Disassembly for cleaning, etc. is exactly the opposite of assembly. Again, be careful of the spring popping out at you, but the mag extension will slide forward far enough to come apart without damaging the spring. Thank you! If you have any questions or problems, the best way to contact us is by email at info@lakelinellc.com

